

#### **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATIO. International Bureau

# INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 00/05533 (11) International Publication Number: (51) International Patent Classification 6: 3 February 2000 (03.02.00) (43) International Publication Date: F16L 59/12

(21) International Application Number:

PCT/AU99/00562

(22) International Filing Date:

8 July 1999 (08.07.99)

(30) Priority Data: PP 4832

23 July 1998 (23.07.98)

ΑU

(71) Applicant (for all designated States except US): BAINS HARDING LIMITED [AU/AU]; 21 King Edward Road, Osborne Park, W.A. 6017 (AU).

(72) Inventors; and

(75) Inventors; and (75) Inventors/Applicants (for US only): KEENAN, Brian [AU/AU]; 18 St. Michaels Terrace, Mt. Pleasant, W.A. 6153 (AU). VUJIC, Milivoj [AU/AU]; 24 Wheyland Street, Willagee, W.A. 6156 (AU).

(74) Agent: WATERMARK PATENT & TRADEMARK ATTOR-NEYS; Durack Centre, 4th Floor, 263 Adelaide Terrace, Perth, W.A. 6000 (AU).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published

With international search report.

NE, SN, TD, TG).

(54) Title: INSULATION MODULE FOR VESSELS



#### (57) Abstract

Described is an insulation module (1) for a vessel (2) used in a chemical plant. The module may take the form of a panel having an outer surface layer (3) and an insulation layer (5) secured to the outer surface layer (3). Mounting means (10) extends from the panel (1) and enables mounting of the insulation module (1) on an outer wall (2) of the vessel. An air gap (15) is provided between the insulation layer (3) and the outer surface layer (4) and the outer surface layer (4) and the outer surface layer (5) are surface layer (6) and an insulation layer (5) secured to the outer surface layer (6) and an insulation layer (7) are surface layer (8) and an insulation layer (8) are surface layer (9) and an insulation layer (9) are surface layer (9) and an insulation layer (9) are surface layer (10) and an insulation layer (10) are surface layer (10) are surfac layer (3) and the outer vessel wall (2) when the insulation module is mounted (1) on the vessel (2).

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑÜ	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Мопасо	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
Cl	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

1

#### **INSULATION MODULE FOR VESSELS**

#### Field of the Invention

The present invention generally relates to insulation technology used in industrial and other applications, and in particular, to an insulation module for insulating a vessel, and a method of installing the insulation module. The present invention will be described with reference to its use on vessels used in chemical plants. It should however be appreciated that other applications of the insulation module are also envisaged.

#### Background to the Invention

In chemical plants, tanks and other vessels holding or carrying materials such as solids, gases or liquids generally need to be maintained within controlled temperature limits for efficient use within the process being conducted within the chemical plant. One way of providing this temperature control is to provide insulation on the vessels and pipes of the plant.

The insulation of a chemical plant is however an expensive and time consuming process. In the case of vessels, a commonly used method of installing the insulation is to initially embed a series of pins over the surface of the outer wall of the vessel with each pin extending laterally therefrom. The insulation material can then be supported on the pins, with a sealing washer being provided at the end of each pin to retain the insulation and any retaining mesh in position. An outer metal cladding is then installed over the top of the insulation to provide protection for the insulation.

The current installation process therefore involves a series of steps. It is not, however, always possible to install pins, as for example in the case of thermally relieved vessels. Other means, such as straps, are then required to hold the insulation in position.

Furthermore, because the insulation material generally used is made of fibrous material such as, for example, fibreglass, the insulation of this material can pose a safety risk to the workers on site such that all non-insulation work must cease while the insulation is being installed. This may necessitate working in night environments where the cost of lighting and incidental costs of employment are commensurately higher than during the day.

Furthermore, because the insulation material is installed immediately against the outer wall surface of the vessel, and because the insulation material can retain moisture, this can potentially lead to corrosion problems for the vessel.

#### 5 Summary of the Invention

It is therefore an object of the present invention to avoid at least one of the above-noted disadvantages of existing insulation systems.

With this object in view, according to one aspect of the present invention, there is provided an insulation module for a vessel including

a panel having an outer surface layer, and an insulation layer secured to the outer surface layer; and

mounting means extending from the panel for enabling mounting of the insulation module on an outer wall of the vessel, wherein an air gap is provided between the insulation layer and the outer wall of the vessel when the insulation module is mounted relative thereto.

The provision of the air gap leads to a number of advantages:

- (a) because the insulation layer is separated from the wall of the vessel by the air gap, this minimises the possibility of corrosion due to the retention of moisture within the insulation layer.
- 20 (b) the air located within the air gap provides an additional insulation layer. This means that the insulation layer secured to the outer surface layer can be of a reduced thickness.

Furthermore, because the insulation layer is secured to the outer surface layer prior to insulation of the insulation module, the insulation layer can be treated to prevent the release of potentially hazardous fibres therefrom. For example, the insulation layer may be covered by material prior to securing to the outer surface layer. Alternatively, an adhesive paint may be sprayed on the outer surface of the insulation layer to prevent or minimise the release of fibres from that layer prior to securing to the outer surface layer. The Applicant's copending Australian Patent Application No. 26034/99 discloses a suitable sealing agent for this application of reducing fibre release.

The outer surface layer is dependent on the requirements of the plant

WO 00/05533 PCT/AU99/00562

operator. For example, the outer layer may be a corrugated sheet such as "Spandeck" (trademark) or may be a flat sheet. This outer layer can be made of steel or aluminium although other materials are also envisaged.

3

The insulation layer may be secured to the outer surface layer by securing means. For example, the insulation layer may be retained between the outer surface layer and a support mesh. Fastening means may extend between the outer surface layer through the insulation layer to the supporting mesh. The fastening means may for example be in the form of a fixing screw extending from the outer surface layer and through the insulation layer and the support mesh. A speed clip member may be secured to a free end of each fixing screw to retain the support mesh, and therefore the insulation layer in position against the outer surface layer.

According to another possible arrangement, the insulation layer may be adhered directly to the outer surface layer.

The mounting means may include a series of brackets secured to and extending from the outer surface layer towards the vessel wall when the insulation module is in an installed position. Each bracket may include a mounting leg for supporting the panel of the insulation module away from the vessel wall.

Vessels used in chemical plants typically have a series of cleats provided about the outer wall of the vessel to allow cladding to be fixed to the outside of the vessel. To this end, the bracket mounting legs may be secured to the cleats when installing each insulation module on the vessel. Each mounting can be bolted to or welded to a respective cleat. Alternatively, where no cleats are provided, the bracket mounting legs may be welded directly to the vessel wall. Alternatively, fastening means may specifically be provided to secure the bracket mounting legs to the vessel wall. For example, a series of thread rod stubs may be welded to the vessel wall. Each bracket mounting leg may include at least one laterally extending foot having at least one opening therethrough to accommodate a respective thread rod stub. A nut may then be screwed onto each thread and stub to hold the bracket, and therefore the insulation module in position.

4

PCT/AU99/00562

The insulation layer may be made of a variety of different material and may be of different thickness. For example, rock wool, fibreglass, PIR foam or PUR foam and mixtures thereof could be used for the insulation layer. Fire retardants may be incorporated therein. The present invention is not restricted 5 by the insulation material used in the insulation layer.

The insulation modules may be installed in an abutting or closely adjacent relationship to form a matrix covering at least a substantial portion of the outer wall of the vessel and thereby provide the necessary insulation for that vessel. Insulation may also be provided for conical sections of vessels. The 10 present invention therefore eliminates the need to embed pins within the outer wall of the vessel. Furthermore, the installation procedure is a less time consuming single step process. In addition, maintenance of the installation is facilitated because individual modules can be readily removed and replaced with new modules as so required.

According to another aspect of the present invention, there is provided a method of installing insulation on a vessel including mounting a plurality of insulation modules in an abutting or closely adjacent relationship on an outer surface of the vessel, each insulation module including a panel having an outer surface layer, and an insulation layer secured to the outer surface layer, and 20 mounting means extending from the panel for mounting the insulation module on the outer wall of the vessel, wherein the method includes securing the mounting means to the vessel to thereby provide an air gap between the insulation layer and the outer wall of the vessel when the insulation modules are mounted relative thereto.

25 According to yet another aspect of the present invention, there is provided an insulated vessel including a series of insulation modules as described above mounted in an abutting or closely adjacent relationship on an outer surface of the vessel.

#### Brief Description of the Drawings

15

30 The various aspects of the invention may be more completely understood from the following description of an example arrangement of the present invention with reference to the accompanying drawings in which:

5

Figure 1 is a cross-sectional view of an insulation module according to the present invention; and

Figure 2 is a detailed partial cross-sectional view of the insulation module of Figure 1 mounted on a vessel wall.

#### 5 <u>Detailed Description of Preferred Embodiment of the Invention</u>

The insulation module 1 includes a panel having an outer surface layer 3 formed, for example, from at least one sheet of "Spandeck" (trade mark). The use of other sheet material is possible depending on client requirements. An insulation layer 5 is secured to the underside of the outer surface layer 3. This insulation layer 5 can be of any one of a number of different materials. For example, the insulation layer 5 can be provided by sheets of rock wool covered by a material layer to prevent the release of fibres from the rock wool. Alternatively, the rock wool could be replaced with fibreglass. In any event, release of fibres may be prevented by sealing the fibrous material stock with a sealing agent, perhaps an acrylic emulsion. Use of sealing agents for this application is described in the Applicant's co-pending Australian Patent Application No. 26034/99, filed 30th April, 1999, the contents of which are hereby incorporated by reference.

The insulation layer 5 is secured to the outer surface layer 3 by means of a series of fixing screws 10 inserted through the outer surface layer 3 and the insulation layer 5. A sealing washer 11 is located between the head of the fixing screw 10 and the outer surface layer 3. A sheet of wire mesh 18 is provided on the opposing side of the insulation layer 5 to help to support that layer 5. An end of the fastening screw 10 extends through the wire mesh 18, and a speed clip 12 is attached to the end of each fixing screw 10 to hold the wire mesh 18, and therefore the insulation layer 5 in position.

The insulation module 1 further includes a series of brackets 7. Each bracket 7 includes an upper end 9 shaped to conform with the general profile of the Spandeck sheet 3. Adjacent sheets 3 overlap along their respective edge portions. These sheets 3 are then secured to the bracket 7 by means of a further fixing screw 13 extending through the overlapping edge portions of the sheets 3 and the bracket upper end 9. A further sealing washer 14 is located between

WO 00/05533 PCT/AU99/00562

the head of the further fixing screw 13 and the Spandeck sheets 3.

5

Each bracket 7 further includes a mounting leg 8 which extends through the insulation layer 5 and the wire mesh 18 and extends beyond the assembled panel 6 of the insulation module 1.

6

A series of cleats 16 are typically provided along the exterior surface 17 of the vessel wall 2. The bracket 7 of the insulation module 1 are spaced along the insulation module 1 and correspond with the spacing of the cleats 16 on the vessel wall 2. The mounting leg 8 of each bracket 7 can then be secured to a respective cleat 16 to install the insulation module 1. The brackets 7 can be 10 welded to or bolted to the cleats 16. Alternatively, where no cleats are provided, then the brackets 7 can be welded to the vessel wall 2.

A series of the insulation modules 1 can be installed in an abutting or closely adjacent relationship over the outer surface 17 of the vessel wall 2 to thereby at least substantially cover the vessel wall and thereby provide the 15 necessary insulation for that vessel. Because the bracket 7 extends beyond the insulation module panel 6, an air gap 15 is provided between the insulation layer 5 and the vessel wall 2. This air gap 15 leads to the advantages described above.

It is also envisaged according to the present invention that the panel 6 of 20 the insulation module 1 be formed from an outer surface layer having an insulation layer bonded directly to the outer surface layer.

Modifications and variations may be made to the present invention or consideration of the disclosure by the skilled reader of this disclosure. Such modifications and variations are considered to fall within the scope of the 25 present invention.

#### THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:


1. An insulation module for a vessel including:


a panel having an outer surface layer, and an insulation layer secured to the outer surface layer; and mounting means extending from the panel for enabling mounting of the insulation module on an outer wall of the vessel, wherein an air gap is provided between the insulation layer and the outer wall of the vessel when the insulation module is mounted relative thereto.

- 2. The insulation module of claim 1 wherein said insulation layer is a fibrous material treated to prevent escape of fibres.
- 3. The insulation module of claim 1 or 2 wherein said insulation layer is retained between the outer surface layer and a support mesh.
- 4. The insulation module of claim 3 wherein fastening means extend between the outer surface layer through the insulation layer to the supporting mesh.
- 5. The insulation module of claim 4 wherein said fastening means is at least one fixing screw.
- 6. The insulation module of claim 5 wherein a speed clip member is secured to a free end of said at least one fixing screw.
- 7. The insulation module of any one of the preceding claims wherein the insulation layer is adhered directly to the outer surface layer.
- 8. The insulation module of any one of the preceding claims wherein said mounting means includes a series of brackets secured to and extending from the outer surface layer towards the vessel wall when the insulation is in an installed position.

- 9. The insulation module of claim 8 wherein each bracket includes a mounting leg for supporting the panel of the insulation module away from the vessel wall.
- 10. •The insulation module of claim 9 wherein said vessel has a series of cleats provided about the outer wall thereof and said mounting legs of said brackets are secured to said cleats.
- 11. The insulation module of claim 9 wherein fastening means secure said bracket mounting legs to the vessel wall.
- 12. The insulation module of claim 11 wherein said fastening means are thread rod stubs and each bracket mounting leg includes at least one laterally extending foot having at least one opening therethrough to accommodate respective thread rod stubs.
- 13. The insulation module of any one of the preceding claims wherein said insulation layer is of material selected from the group consisting of rock wool, fibreglass, PIR foam, PUR foam and mixtures thereof.
- 14. A method of installing insulation on a vessel including mounting a plurality of insulation modules, each as claimed in any one of claims 1 to 13, in an abutting or closely adjacent relationship on an outer surface of the vessel, each insulation module including a panel having an outer surface layer, and an insulation layer secured to the outer surface layer, and mounting means extending from the panel for mounting the insulation module on an outer wall of the vessel, wherein the method includes securing the mounting means to the vessel to thereby provide an air gap between the insulation layer and the outer wall of the vessel when the insulation modules are mounted relative thereto.
- 15. The method of claim 14 wherein said insulation layer is of fibrous material treated to prevent release of fibres.


- 16. The method of claim 15 wherein said fibrous material is treated with a sealing agent, optionally an acrylic emulsion.
- 17. The method of any one of claims 14 to 16 wherein said outer surface of said vessel includes the outer surface of a conical section thereof.
- 18. A vessel insulated in accordance with the method of any one of claims 14 to 17.





International application No.
PCT/AU 99/00562

		PCI	7AU 99/00562
Α.	CLASSIFICATION OF SUBJECT MATTER	<u> </u>	
Int Cl6:	F16L 59/12		
According to	International Patent Classification (IPC) or to bo	th national classification and IPC	
В.	FIELDS SEARCHED		
Minimum doc IPC:F16L 5	umentation searched (classification system followed by 9/12	classification symbols)	
Documentation AU:IPC as	n searched other than minimum documentation to the eabove	xtent that such documents are included i	n the fields searched
Electronic data	a base consulted during the international search (name of	of data base and, where practicable, search	ch terms used)
C.	DOCUMENTS CONSIDERED TO BE RELEVAN	T	
Category*	Citation of document, with indication, where ap	opropriate, of the relevant passages	Relevant to claim No.
х	DE, 3906708, A (P'ARTEK CORP) 6 December See entire Specification	er 1990	1,7,8,9,14
x	US 4436119, A (SHAHAN ET AL) 13 March 1 See entire Specification	1984	1,2,7,8,9,14,15
x	US 4122640 A (COMMINS ET. AL.) 31 Octob See entire Specification	per 1978	1,7,8,14
X	Further documents are listed in the continuation of Box C	X See patent family	annex
"A" docum not co "E" earlier the int docum or wh anothe "O" docum or oth "P" docum	nent defining the general state of the art which is ensidered to be of particular relevance repplication or patent but published on or after ternational filing date enent which may throw doubts on priority claim(s) ich is cited to establish the publication date of er citation or other special reason (as specified) enent referring to an oral disclosure, use, exhibition er means	later document published after the priority date and not in conflict wounderstand the principle or theory document of particular relevance; be considered novel or cannot be inventive step when the document document of particular relevance; be considered to involve an inventive step with one or more other combined with one or more other combination being obvious to a pedocument member of the same pat	th the application but cited to underlying the invention the claimed invention cannot considered to involve an is taken alone the claimed invention cannot ive step when the document is such documents, such rson skilled in the art
_	ual completion of the international search	Date of mailing of the international se	arch report
4 August 1999		10 AUG 1999	
AUSTRALIAN PO BOX 200 WODEN ACT	ing address of the ISA/AU I PATENT OFFICE 2606	Authorized officer  R. WEBER	
AUSTRALIA Facsimile No.:	(02) 6285 3929	Telephone No.: (02) 6283 2546	



... cernational application No.

PCT/AU 99/00562

C (Continua	tion). DOCUMENTS CONSIDERED TO BE RELEVANT	<del>,</del>
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Α	DE 19631291 A (DAMPERS ENGINEERING GmBH) 5 February 1998 See entire Specification	-
x	AU 13469/95 A (TRI-FORM AUSTRALIA PTY, LTD.) 31 August 1995 See entire Specification	1,8,9,11,12,1
x	DE 4225448 A (JANICH GmbH & Co) 3 February 1994 See entire Specification	1,14
x	Derwent Abstract Accession No. 85054566/09 Class Q67 SU 1104339 a (ANDLEEV VA) 23 July 1984 See entire Abstract	1,4
	Derwent Abstract Accession No. H2896C/34 Class Q21 SU 706271 A (ZHDANOVTYAZ HMASH) 31 December 1979 See entire Abstract	
Х	Derwent Abstract Accession No. 90-236876/81 Class Q67 SE 8804482 (ABB CARBBN AB) 13 June 1990	1,14
X	See entire Abstract	1,14
x	Derwent Abstract Accession No. 96-114330/12 Class 67 JP 08014483 A (SANYO ELECTRIC CO. LTD) 16 January 1996 See entire Abstract	1,14
A	FR 2613814 A (BERTIN & CIE, S, A) 14 October 1988 See entire Specification	
Α	DD 203591 A (FRITZSCHE et al) 26 October 1983 See entire Specification	



Information on patent family members

International application No. PCT/AU 99/00562

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Do	cument Cited in S Report	earch		Patent	Family Member		
US	4122640	DE	2835061	GB	2003215	JР	54048316
						<u></u>	
							END OF ANNE

From the:

INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

To:

WATERMARK PATENT & TRADEMARK ATTORNEYS Locked Bag 5

HAWTHORN VIC 3122

PCT

NOTIFICATION OF TRANSMITTAL OF INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Rule 71.1)

IMPORTANT NOTIFICATION

Date of mailing day/month/year

21 DEC 2000

Applicant's or agent's file reference

P16178 P COO RHB:JAM

International application No.

International filing date 8 July 1999

Priority date 23 July 1998

Applicant

AU 99/00562

- BAINS HARDING LIMITED et al
- 1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
- 2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
- 3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translations to those Offices.
- 4. **REMINDER**

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices)(Article 39(1))(see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide

Name and mailing address of the IPEA/AU

**AUSTRALIAN PATENT OFFICE** 

PO BOX 200

WODEN ACT 2606 AUSTRALIA

E-mail address: pct@ipaustralia.gov.au

Facsimile No.: (02) 6285 3929

Authorized officer

R. WEBER

Telephone No. (02) 6283 2546



To:

From	the	INI	FRN	ΙΔΤ	<b>ION</b>	ΔI	RUI	RFA	u
FIGIL	me	113		.~ .	IUII	$\sim$	UUI	$\cdot \cdot \cdot - \cdot$	•

#### **PCT**

#### **NOTIFICATION OF ELECTION**

(PCT Rule 61.2)

Assistant Commissioner for Patents United States Patent and Trademark Office

Box PCT

Washington, D.C.20231 ÉTATS-UNIS D'AMÉRIQUE

Date of mailing (day/month/year) 18 February 2000 (18.02.00)	in its capacity as elected Office
International application No. PCT/AU99/00562	Applicant's or agent's file reference
International filing date (day/month/year) 08 July 1999 (08.07.99)	Priority date (day/month/year) 23 July 1998 (23.07.98)
Applicant  KEENAN, Brian et al	

1.	The designated Office is hereby notified of its election made:
	X in the demand filed with the International Preliminary Examining Authority on:
	28 January 2000 (28.01.00)
	in a notice effecting later election filed with the International Bureau on:
2.	The election X was
	was not
	made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Authorized officer

Juan Cruz

Telephone No.: (41-22) 338.83.38

Facsimile No.: (41-22) 740.14.35




# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference P16178 P COO RHB:JAM	FOR FURTHER ACTION		f Transmittal of International Preliminary rt (Form PCT/IPEA/416).
International application No.	International filing date	(day/month/year)	Priority Date (day/month/year)
AU 99/00562	8 July 1999		23 July 1998
International Patent Classification (IPC)	or national classification	and IPC	
Int. Cl. <sup>7</sup> F16L 59/12		· Y	
Applicant  1. BAINS HARDING LIMITI	ED et al		
This international preliminary and is transmitted to the application.	examination report has b ant according to Article	seen prepared by this	International Preliminary Examining Authority
2. This REPORT consists of a to	tal of 4 sheets, including	ng this cover sheet.	
X This report is also accome been amended and are the Rule 70.16 and Section 6	e basis for this report and	d/or sheets containir	cription, claims and/or drawings which have ag rectifications made before this Authority (see the PCT).
These annexes consist of a total	al of 5 sheet(s).		
3. This report contains indications relation	ng to the following items	:	*
I X Basis of the repor	t		·
II Priority			
III Non-establishmer	at of opinion with regard	to novelty, inventive	e step and industrial applicability
IV Lack of unity of it	nvention		·
V X Reasoned stateme citations and expl	ent under Article 35(2) wantions supporting such	rith regard to novelty a statement	, inventive step or industrial applicability;
VI Certain document	s cited		
VII Certain defects in	the international applica	tion .	
VIII X Certain observation	ons on the international a	pplication	
	1_		
Date of submission of the demand 28 January 2000		ate of completion of B December 2000	the report
Name and mailing address of the IPEA/A	AU A	uthorized Officer	1
AUSTRALIAN PATENT OFFICE PO BOX 200			
WODEN ACT 2606 AUSTRALIA E-mail address: pct@ipaustralia.gov.au	R	. WEBER	
Facsimile No. (02) 6285 3929		elephone No. (02) 6	283 2546

#### INTERNATIONAL PRELIMINARY EXAMINATION REPORT



I.		Basis of the repo	ort
1.	With	regard to the elem	ents of the international application:*
		the international a	application as originally filed.
٠	X	the description,	pages 1, 3-6, as originally filed, pages , filed with the demand, pages 2, 2a, received on 17 July 2000 with the letter of 17 July 2000.
	X	the claims,	pages , as originally filed, pages , as amended (together with any statement) under Article 19, pages , filed with the demand, pages 7, 7a-9, received on 17 July 2000 with the letter of 17 July 2000.
	X	the drawings,	pages 1, 2, as originally filed, pages , filed with the demand, pages , received on with the letter of .
		the sequence listing	pages , as originally filed pages , filed with the demand pages , received on with the letter of .
2	which	h the international a	tage, all the elements marked above were available or furnished to this Authority in the language in application was filed, unless otherwise indicated under this item.  The following language which is:
		the language of a	translation furnished for the purposes of international search (under Rule 23.1(b)).
		the language of pu	ablication of the international application (under Rule 48.3(b)).
		the language of th and/or 55.3).	e translation furnished for the purposes of international preliminary examination (under Rules 55.2
3.		regard to any nucle	eotide and/or amino acid sequence disclosed in the international application, was on the basis of the
		contained in the ir	nternational application in written form.
		filed together with	the international application in computer readable form.
	$\Box$	furnished subsequ	ently to this Authority in written form.
		furnished subsequ	ently to this Authority in computer readable form.
			t the subsequently furnished written sequence listing does not go beyond the disclosure in the cation as filed has been furnished.
			t the information recorded in computer readable form is identical to the written sequence listing has
4.		The amendments l	have resulted in the cancellation of:
		the descrip	tion, pages
		the claims,	Nos.
		the drawing	gs, sheets/fig
5.		go beyond the disc	en established as if (some of) the amendments had not been made, since they have been considered to closure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).**
*	report	as "originally filed"	have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).
**	Any re	eplacement sheet cont	aining such amendments must be referred to under item 1 and annexed to this report

V.	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial
	applicability; citations and explanations supporting such statement

1.	Statement
----	-----------

Novelty (N)	3-7, 10, 13, 15-18 1, 8, 9, 11, 12, 14	NO
Inventive step (IS)	10, 17	YES

Claims 1-9, 11-16, 18

Industrial applicability (IA) Claims 1-18
Claims NO

2. Citations and explanations (Rule 70.7)

#### NOVELTY (N) Claims 1, 8, 9, 11, 12, 14

#### AU 13469/95 A

The above citation discloses all the features of the claims listed above.

This citation is directed to insulating structures per se (the wall of a dwelling being merely one example) and which would include process vessels.

The citation is directed not to a specific field of applications but rather to a desired result an hence a person considering insulating the process vessel would consider this document relevant.

# INVENTIVE STEP (IS) Claims 1 to 9, 11 to 16, 18


Claims 1, 8, 9, 11, 12, 14 as above.

Claims 2 to 7, 13, 15, 16, and 18: the features added by these claims amount to common general knowledge and hence do not involve an inventive step.

### INDUSTRIAL APPLICABILITY (IA) Claims 1 to 18

All claims are considered to be industrially applicable.

#### INTERNATIONAL PRELIMINARY EXAMINATION REPORT



### VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

- 1. Claim 1 is not clear with regard to the phase beginning "none of which..." and where the limitation ends. Do the fastening components not only not extend continuously about the periphery but also not space from the outer wall.
- 2. Claim 1 is not clear with regard to the relationship between the outer surface layer of the panel and the thermal insulation layer and the process vessel. That is on which side of the panel is the thermal insulation and is the panel of the thermal insulation closest to the process vessel.
- 3. Claim 17 is not clear with regard to the phrase "the outer surface of a conical section there of" and what this is referring to.

09 (744351 . - .



# CORRECTED VERSION

# **PCT**

# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

15

Applicant's or agent's file reference P16178 P COO RHB:JAM	FOR FURTHER ACTION	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416).			
International application No.  International filing (day/month/year)		<b>x</b> c	Priority Date (day/month/year)		
AU 99/00562	8 July 1999		23 July 1998		
International Patent Classification (IPC	) or national classification	on and IPC			
Int. Cl. <sup>7</sup> F16L 59/12	<u>-</u>				
Applicant 1. BAINS HARDING LIMIT	ED et al				
1. This international preliminary	y examination report has	been prepared by the	nis International Preliminary Examining		
Authority and is transmitted to	o the applicant according	g to Article 36.			
2. This REPORT consists of a to	tal of 3 sheets, includi	ng this cover sheet.			
X This report is also accombeen amended and are the (see Rule 70.16 and Sec	he basis for this report a	nd/or sheets contain	scription, claims and/or drawings which have ing rectifications made before this Authority under the PCT).		
These annexes consist of a tot	al of 5 sheet(s).				
3. This report contains indications relat	ing to the following item	n\$:			
I X Basis of the repor	r <b>t</b>				
II Priority					
III Non-establishmer	at of opinion with regard	l to novelty, inventiv	ve step and industrial applicability		
IV Lack of unity of i	nvention		·		
V X Reasoned stateme citations and exp	ent under Article 35(2) was lanations supporting suc	vith regard to novelt h statement	y, inventive step or industrial applicability;		
VI Certain document	ts cited				
VII Certain defects in	the international applic	ation			
VIII X Certain observation	ons on the international	application			
Date of submission of the demand 28 January 2000		Date of completion of the report 18 December 2000			
Name and mailing address of the IPEA	'AU A	Authorized Officer			
AUSTRALIAN PATENT OFFICE PO BOX 200					
WODEN ACT 2606 AUSTRALIA	.  _				
E-mail address: pct@ipaustralia.gov.au Facsimile No. (02) 6285 3929		R. WEBER Telephone No. (02) 6283 2546			

Form PCT/TPFA/409 (Cover sheet) (July 1998) COPSAOCOPSAO

٠			
7	International	application	No.

PCT/AU 99/00562

I.	•	Basis of the repor	t
1.	With	regard to the eleme	ents of the international application:*
		the international a	pplication as originally filed.
	X	the description,	pages 1, 3-6, as originally filed, pages , filed with the demand, pages 2, 2a, received on 17 July 2000 with the letter of 17 July 2000.
	X	the claims,	pages , as originally filed, pages , as amended (together with any statement) under Article 19, pages , filed with the demand, pages 7-9 received on 22 August 2000 with the letter of 22 August 2000.
	X	the drawings,	pages 1, 2, as originally filed, pages , filed with the demand, pages , received on with the letter of .
		the sequence listin	g part of the description:
			pages , as originally filed  pages , filed with the demand  pages , received on with the letter of .
2.	whic.	h the international a	age, all the elements marked above were available or furnished to this Authority in the language in pplication was filed, unless otherwise indicated under this item. ilable or furnished to this Authority in the following language which is:
		the language of a t	ranslation furnished for the purposes of international search (under Rule 23.1(b)).
			blication of the international application (under Rule 48.3(b)).
		the language of the and/or 55.3).	translation furnished for the purposes of international preliminary examination (under Rules 55.2
3.	With the se	regard to any nucle	otide and/or amino acid sequence disclosed in the international application, was on the basis of
		contained in the in	ternational application in written form
		filed together with	the international application in computer readable form.
			ently to this Authority in written form.
		furnished subseque	ently to this Authority in computer readable form.
		The statement that	the subsequently furnished written sequence listing does not go beyond the disclosure in the cation as filed has been furnished.
			the information recorded in computer readable form is identical to the written sequence listing has
4.		The amendments 1	resulted in the cancellation of:
		the descript	ion, pages
		the claims,	Nos.
		the drawing	s, sheets/fig
5.		to go beyond the di	on established as if (some of) the amendments had not been made, since they have been considered sclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).**
•	Repla	cement sheets which h as "originally filed" a	ave been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).
**	Any re	placement sheet conto	sining such amendments must be referred to under item 1 and annexed to this report

International application No. PCT/AU 99/00562

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicable citations and explanations supporting such statement	ility;
--	--------

1.	Statement			
	Novelty (N)	Claims Claims		YES NO
	Inventive step (IS)	Claims Claims	1-18	YES NO
	Industrial applicability (IA)	Claims Claims	1-18	YES NO

2. Citations and explanations (Rule 70.7)

#### NOVELTY (N) and INVENTIVE STEP (IS) Claims 1-18

The closest art is found in AU 13469/95 A (Tri-Form) 31 August 1995 wherein is disclosed a method of insulating a structure such that the insulating layer is held at a predetermined distance from the structure thereby allowing the formation of an air-gap between the two. The insulated system so obtained, however, is not one which involves a "process vessel for containing a material to be maintained within controlled temperature limits for use in a process" and the mounting means disclosed in this citation do not "comprise a fastening system of complementary fastening components, none of which extend continuously about a/the periphery of the process vessel".

As a result the invention as claimed in claims 1-18 is considered to be novel and to involve an inventive step in the light of this document.

#### INDUSTRIAL APPLICABILITY (IA) Claims 1 to 18

All claims are considered to have industrial applicability.

Form PCT/IPEA/409 (Box V) (July 1998) COPSAO

### VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

- 1. Claim 1 is not clear with regard to the phase beginning "none of which..." and where the limitation ends. Do the fastening components not only not extend continuously about the periphery but also not space from the outer wall.
- 2. Claim 1 is not clear with regard to the relationship between the outer surface layer of the panel and the thermal insulation layer and the process vessel. That is on which side of the panel is the thermal insulation and is the panel of the thermal insulation closest to the process vessel.
- 3. Claim 17 is not clear with regard to the phrase "the outer surface of a conical section there of" and what this is referring to.

Furthermore, because the insulation material is installed immediately against the outer wall surface of the vessel, and because the insulation material can retain moisture, this can potentially lead to corrosion problems for the vessel. Summary of the Invention

It is therefore an object of the present invention to avoid at least one of the above-noted disadvantages of existing insulation systems.

5

With this object in view, according to one aspect of the present invention, there is provided an insulation module for a process vessel including

an externally mounted pre-fabricated panel having integrally formed therein 10 an outer surface layer, and a thermal insulation layer which opposes a portion of an outer wall of the process vessel; and

mounting means comprising a fastening system of complementary fastening components, none of which extend continuously about a periphery of the process vessel extending from the panel to the vessel for directly mounting the panel at a distance from the outer wall of the process vessel, to define an air gap between the panel and the outer wall of the process vessel when the insulation module is mounted relative thereto.

The provision of the air gap leads to a number of advantages:

- (a) because the insulation layer is separated from the wall of the vessel 20 by the air gap, this minimises the possibility of corrosion due to the retention of moisture within the insulation layer
  - (b) the air located within the air gap provides an additional insulation layer. This means that the insulation layer secured to the outer surface layer can be of a reduced thickness.
- Furthermore, because the insulation layer is secured to the outer surface layer prior to insulation of the insulation module, the insulation layer can be treated to prevent the release of potentially hazardous fibres therefrom. For example, the insulation layer may be covered by material prior to securing to the outer surface layer. Alternatively, an adhesive paint may be sprayed on the outer surface of the insulation layer to prevent or minimise the release of fibres from that layer prior to securing to the outer surface layer. The applicant's co-pending

AMENDED SHEET

2a

Australian Patent Application No. 26034/99 discloses a suitable sealing agent for this application of reducing fibre release.

The outer surface layer is dependent on the requirements of the plant

AMENDED SHEET IPENAU

### THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An insulation module for a process vessel for containing a material to be maintained within controlled temperature limits for use in a process including:

an externally mounted pre-fabricated panel having integrally formed therein an outer surface layer and a thermal insulation layer which opposes a portion of the outer wall of the process vessel; and

mounting means comprising a fastening system of complementary fastening components, none of which extend continuously about the periphery of the process vessel, for directly mounting the panel at a distance from the outer wall of said process vessel to define an air gap between the panel and the outer wall of the process vessel when the insulation module is mounted relative thereto.

- 2. The insulation module of claim 1 wherein said insulation layer is a fibrous material treated to prevent escape of fibres.
- 3. The insulation module of claim 1 or 2 wherein said insulation layer is retained between the outer surface layer and a support mesh.
- 4. The insulation module of claim 3 wherein fastening means extend between the outer surface layer through the insulation layer to the supporting mesh.
- 5. The insulation module of claim 4 wherein said fastening means is at least one fixing screw.
- 6. The insulation module of claim 5 wherein a speed clip member is secured to a free end of said at least one fixing screw.
- 7. The insulation module of any one of the preceding claims wherein the insulation layer is adhered directly to the outer surface layer of said panel.

AMENDED SHEET

HILFU

- 8. The insulation module of any one of the preceding claims wherein said mounting means includes a series of brackets secured to and extending from the outer surface layer towards the vessel wall when the insulation is in an installed position.
- 9. The insulation module of claim 8 wherein each bracket includes a mounting leg for supporting the panel of the insulation module away from the vessel wall.
- 10. The insulation module of claim 9 wherein said vessel has a series of cleats provided about the outer wall thereof and said mounting legs of said brackets are secured to said cleats.
- 11. The insulation module of claim 9 wherein fastening means secure said bracket mounting legs to the vessel wall.
- 12. The insulation module of claim 11 wherein said fastening means are thread rod stubs and each bracket mounting leg includes at least one laterally extending foot having at least one opening therethrough to accommodate respective thrread rod stubs.
- 13. The insulation module of any one of the preceding claims wherein said insulation layer is of material selected from the group consisting of rock wool, fibreglass, PIR foam, PUR form and mixtures thereof.
- 14. A method of installing insulation on a process vessel for containing a material to be maintained within controlled temperature limits for use in a process including mounting a plurality of insulation modules, each as claimed in any one of claims 1 to 13 in an abutting or closely adjacent relationship on an outer surface of the vessel, each insulation module including a panel having an outer surface layer, and an insulation layer secured to the outer surface layer, and mounting means extending from the panel for mounting the insulation module on

AMENDED SHEET IPEA/AU

9

an outer wall of the vessel, wherein the method includes securing the mounting means to the vessel to thereby provide an air gap between the insulation layer and the outer wall of the vessel when the insulation modules are mounted relative thereto.

- 15. The method of claim 14 wherein said insulation layer is of fibrous material treated to prevent release of fibres.
- 16. The method of claim 15 wherein said fibrous material is treated with a sealing agent, optionally an acrylic emulsion.
- 17. The method of any one of claims 14 to 16 wherein said outer surface of said vessel includes the outer surface of a conical section of the vessel.
- 18. A process vessel insulated in accordance with the method of any one of claims 14 to 17.

<u>DATED</u> this 21<sup>51</sup> day of August, 2000 <u>BAINS HARDING LIMITED</u>

WATERMARK PATENT & TRADEMARK ATTORNEYS 4<sup>™</sup> FLOOR "DURACK CENTRE" 263 ADELAIDE TERRACE PERTH WA 6000

International application No. PCT/AU 99/00562

		rci.	AU 99/00562			
Α.	CLASSIFICATION OF SUBJECT MATTE	R				
Int Cl6:	F16L 59/12					
According to	According to International Patent Classification (IPC) or to both national classification and IPC					
B.	FIELDS SEARCHED					
	Minimum documentation searched (classification system followed by classification symbols) IPC:F16L 59/12					
Documentation AU:IPC as	n searched other than minimum documentation to the above	extent that such documents are included in	the fields searched			
Electronic data	a base consulted during the international search (name	of data base and, where practicable, search	i terms used)			
c.	DOCUMENTS CONSIDERED TO BE RELEVAN	NT				
Category*	Citation of document, with indication, where a		Relevant to claim No.			
х	DE, 3906708, A (P'ARTEK CORP) 6 December 1990  X See entire Specification					
x	1,2,7,8,9,14,15					
x	US 4122640 A (COMMINS ET. AL.) 31 Octo See entire Specification	ber 1978	1,7,8,14			
x	Further documents are listed in the continuation of Box C	X See patent family a	nnex			
** Special categories of cited documents:  "A" document defining the general state of the art which is not considered to be of particular relevance  "E" earlier application or patent but published on or after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document of particular relevance; the claimed invention cannot document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents. such combined with one or more other such documents. such combination being obvious to a person skilled in the art document member of the same patent family						
Date of the actual completion of the international search  Date of mailing of the international search report						
4 August 1999		10 AUG 1999				
	ng address of the ISA/AU PATENT OFFICE 2606	Authorized officer  R. WEBER				
USTRALIA		Telephone No.: (02) 6283 2546				
Facsimile No.: (02) 6285 3929 Telephone No.: (02) 6283 2546						

... cernational application No.

PCT/AU 99/00562

CIC	DOCUMENTS CONOR	PCT/AU 99/00562	
C (Continual	ion). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant pas	sages	Relevant to claim No.
Α	DE 19631291 A (DAMPERS ENGINEERING GmBH) 5 February 1998 See entire Specification	<del> </del>	
x	AU 13469/95 A (TRI-FORM AUSTRALIA PTY, LTD.) 31 August 1995 See entire Specification		1,8,9,11,12,1
x	DE 4225448 A (JANICH GmbH & Co) 3 February 1994 See entire Specification		1,14
x	Derwent Abstract Accession No. 85054566/09 Class Q67 SU 1104339 a (AN 23 July 1984 See entire Abstract	IDLEEV VA)	1,4
x	Derwent Abstract Accession No. H2896C/34 Class Q21 SU 706271 A (ZHD. HMASH) 31 December 1979 See entire Abstract	ANOVTYAZ	1,14
x	Derwent Abstract Accession No. 90-236876/81 Class Q67 SE 8804482 (ABE 13 June 1990 See entire Abstract	CARBBN AB)	1,14
x	Derwent Abstract Accession No. 96-114330/12 Class 67 JP 08014483 A (SA CO. LTD) 16 January 1996 See entire Abstract	NYO ELECTRIC	1,14
A	FR 2613814 A (BERTIN & CIE, S, A) 14 October 1988 See entire Specification		
A	DD 203591 A (FRITZSCHE et al.) 26 October 1983 See entire Specification		÷

Information on patent family members

International application No. PCT/AU 99/00562

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

tent Doc	cument Cited in Sea Report	arch	er.	Patent	t Family Member		
US	4122640	DE	2835061	GB	2003215	ЛР	54048316
			•				
	•						
						•	
		-					
-	٠.						
		e.					
		÷ .	e e e e e e e e e e e e e e e e e e e				
		. •					
,		·		•			
			:				
•			-				•
					,	J	END OF ANNE



INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

	··	_			
To: WATERMARK PATENT & TRADEMARK		PCT			
ATTORNEYS Locked Bag 5		WRITTEN OPINION			
HAWTHORN VIC 3122			(PCT Rule 66)		
[g3]					
		Date of mailing (day/month/year)	24 FEBRUARY 2000		
Applicant's or agent's file reference RHB:JCC		REPLY DUE	within TWO MONTHS from the above date of mailing		
International application No.	International filing da	ite (day/month/year)	Priority Date (day/month/year)		
PCT/AU 99/00562	08 July 1999		23 July 1998		
International Patent Classification (IPC) of	both national classif	fication and IPC			
Int. Cl. <sup>7</sup> F16L 59/12					
Applicant					
1: BAINS HARDING LIMITED					
<ol> <li>KEENAN, Brian</li> <li>VUJIC, Milivoj</li> </ol>					
5. VOIC, MINVO					
1. This written opinion is the FIRST	drawn by this Inter	rnational Preliminary l	Examining Authority.		
2. This opinion contains indications rela	ting to the following	items:.			
I Basis of the opinion	,				
II Priority					
III Non-establishment of	pinion with regard to r	novelty, inventive step an	d industrial applicability		
IV Lack of unity of invention					
	nder Rule 66.2(a)(ii) wi		entive step or industrial applicability,		
VI Certain documents cite					
VII Certain defects in the i	nternational application	n			
VIII X Certain observations of	n the international appl	ication	•		
3. The applicant is hereby invited to reply	to this opinion.				
	ted above. The applica	ant may, before the expir	ation of that time limit, request this Authority to		
		here appropriate, by aments, see Rules 66.8 and 6	ndments, according to Rule 66.3.		
	ation to consider amend	dments and/or arguments	, see Rule 66.4 <i>bis</i> .		
For an informal commun		•	shed on the basis of this opinion.		
4. The final date by which the international preliminary examination report must be established					
according to Rule 69.2 is: 23 Novem		·	_//		
Name and mailing address of the IPEA/AU	A	uthorized Officer	/ (		
AUSTRALIAN PATENT OFFICE PO BOX 200		./			
WODEN ACT 2606 AUSTRALIA E-mail address: pct@ipaustralia.gov.au		. WEBER			
L-man address. percepipadistrana.gov.ad	**				

Telephone No. (02) 6283 2546

Facsimile No. (02) 6285 3929




	•		PCT/AU 99/00562
K	Basis of the opinion		
1.	With regard to the elements of the	ne international application:*	
	X The international	application as originally filed.	
	The description,	pages , as originally filed,	
		pages , filed with the demand,	
		pages , filed with the letter of .	
	the claims,	pages , as originally filed,	
		pages , as amended under Article 19,	
		pages , filed with the demand,	
		pages , filed with the letter of .	
	the drawings,	pages , as originally filed,	
		pages , filed with the demand,	
		pages , filed with the letter of .	
	the sequence listing	g part of the description:	
	pages	, as originally filed	
	pages	, filed with the demand	•
	pages	, filed with the letter of .	
2.	which the international application w These elements were available or furn	elements marked above were available or furnished to as filed, unless otherwise indicated under this item. hished to this Authority in the following language furnished for the purposes of international search (u	which is:
		of the international application (under Rule 48.3(b)).	mae: raic 25.1(0)).
			( )
	and/or 55.3).	on furnished for the purposes of international prelimi	nary examination (under Rules 55.2
3.	With regard to any nucleotide and/or drawn on the basis of the sequence list	r amino acid sequence disclosed in the international sting:	application, the written opinion was
	Contained in the internationa	l application in printed form.	
	filed together with the interna	ational application in computer readable form.	· ·
	Furnished subsequently to the	is Authority in written form.	
	Furnished subsequently to the	is Authority in computer readable form.	
	The statement that the subsectinternational application as fi	quently furnished written sequence listing does not go led has been furnished.	beyond the disclosure in the
	been furnished.	nation recorded in computer readable form is identicated	al to the written sequence listing has
4.	The amendments have resulted	ed in the cancellation of:	
	the description,	pages	
	the claims,	Nos.	
	the drawings,	sheets/fig	

\* Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this opinion as "originally filed"

This opinion has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).

5.







Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

Statement

Novelty (N)		3,4,5,6,10,13,16,17,18 1,2,7,8,9,11,12,14,15	YES NO
Inventive step (IS)	Claims Claims	10,17 1 to 9, 11 to 16, 18	YES NO
Industrial applicability (IA)	Claims Claims	1 to 18	YES NO

2. Citations and explanations

#### **NOVELTY(N) CLAIMS 1,2,7,8,9,11,12,14,15**

DE 3906708, A	CLAIMS 1,7,8,9,14
US 4436119, A	CLAIMS 1,2,7,8,9,14,15
US 4122640, A	CLAIMS 1,7,8,14
AU 13469/95, A	CLAIMS 1,8,9,11,12,14
DE 4225448, A	CLAIMS 1,14
SU 1104339, A	CLAIMS 1,14
SU 706271, A	CLAIMS 1,14
SE 8809482, A	CLAIMS 1,14
JP 08014483, A	CLAIMS 1,14

Each of the above citations explicitly discloses all of the features of the claims listed alongside.

### **INVENTIVE STEP(IS) CLAIMS 1 TO 9, 11 TO 16, 18**

Claims 1,2,7,8,9,11,12,14,15 as above.

Claims 3,4,5,6,13,16,18:

The features added by these claims merely amount to common general knowledge and hence do not involve an inventive step.

#### **INDUSTRIAL APPLICABILITY (IA) CLAIMS 1 TO 18**

All claims are considered to be industrially applicable.





International application No.

#### PCT/AU 99/00562



## Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

Claim 17 is not clear with regard to the phrase "the outer surface of a conical section thereof" and what this is referring to.

, P1617820

PATENT COOPERATION TRE

From the: NETERNATIONAL PRELIMINARY EXAMIN	NING AUTHORITY			
To: WATERMARK PATENT & TRADEMARK		PCT		
ATTORNEYS			WRITTEN OPINION	
Locked Bag 5 HAWTHORN VIC 3122		(PCT Rule 66)		
	·	Date of mailing (day/month/year)	16 August 2000	
Applicant's or agent's file reference RHB:JCC		REPLY DUE	within TWO MONTHS from the above date of mailing	
International application No.	International filing date	e (day/month/year)	Priority Date (day/month/year)	
PCT/AU99/00562	8 July 1999	<del></del>	23 July 1998	
International Patent Classification (IPC) of	r both national classifi	cation and IPC		
Int. Cl. <sup>7</sup> F16L 59/12 Applicant				
BAINS HARDING LIMITED	) et al			
Z.M.O.I.M.O.I.VO EMVITED	ctai			
KEENAN, Brian				
	·	<u></u>		
IV  Lack of unity of inventi  V  Reasoned statement uncitations and explanatio  VI  Certain documents cited  VII  Certain defects in the in  VIII  X  Certain observations on	pinion with regard to notion  der Rule 66.2(a)(ii) with ons supporting such state d  nternational application the international applica	ems: velty, inventive step and regard to novelty, inve ment	d industrial applicability  ntive step or industrial applicability;	
3. The applicant is hereby invited to reply	· -	·	· · · · · · · · · · · · · · · · · · ·	
grant an extension, see R	ule 66.2(d).		tion of that time limit, request this Authority to	
How? By submitting a written r For the form and the lang	eply, accompanied, wher tuage of the amendments	e appropriate, by amen , see Rules 66.8 and 66	dments, according to Rule 66.3.	
Also For an additional opportu  For the examiner's obligat  For an informal communi	tion to consider amendm	ents and/or arguments.	see Rule 66.4 <i>bis</i>	
If no reply is filed, the international	preliminary examination	report will be establis	hed on the basis of this opinion.	
4. The final date by which the international according to Rule 69.2 is: 23 November 23 November 25 Nov	preliminary examination ber 2000	n report must be establi	shed	
Name and mailing address of the IPEA/AU	Auth	orized Officer	_//	
AUSTRALIAN PATENT OFFICE	Audi	Olicei		
PO BOX 200, WODEN ACT 2606, AUSTRALI E-mail address: pct@ipaustralia.gov.au Facsimile No. (02) 6285 3929	R. V	<b>WEBER</b> phone No. (02) 6283	3 2546	

Telephone No. (02) 6283 2546





International application No.

# PCT/AU99/00562

	Basis	of the opinion	
1.	With regar	rd to the elements	of the international application:*
	t	he international a	pplication as originally filed.
	X t	he description,	pages 1, 3-6, as originally filed.
		•	pages, filed with the demand,
			pages 2, 2a, received on 17 July 2000 with the letter of 17 July 2000
	X t	he claims,	pages, as originally filed,
			pages , as amended under Article 19,
			pages, filed with the demand,
			pages 7, 7a-9, received on 17 July 2000 with the letter of 17 July 2000
	X tl	he drawings,	pages 1, 2, as originally filed,
			pages , filed with the demand,
			pages , received on with the letter of
	tl tl	he sequence listing	g part of the description:
			pages , as originally filed
			pages , filed with the demand
			pages, received on with the letter of
whic	the interse elements	national application were available or	the elements marked above were available or furnished to this Authority in the language in on was filed, unless otherwise indicated under this item.  furnished to this Authority in the following language which is:
Ļ			ation furnished for the purposes of international search (under Rule 23.1(b)).
L			ion of the international application (under Rule 48.3(b)).
	the lar	nguage of the trans (55.3).	slation furnished for the purposes of international preliminary examination (under Rules 55.2
3. With draw	regard to n on the ba	any nucleotide an asis of the sequenc	d/or amino acid sequence disclosed in the international application, the written opinion was e listing:
	contain	ed in the internati	onal application in printed form.
	filed together with the international application in computer readable form.		
	furnish	ed subsequently to	this Authority in written form.
	furnish	ed subsequently to	this Authority in computer readable form.
	The sta	tement that the sultional application	bsequently furnished written sequence listing does not go beyond the disclosure in the as filed has been furnished.
	The sta	tement that the inf	formation recorded in computer readable form is identical to the written sequence listing has
4.	The am	endments have res	sulted in the cancellation of:
		the description,	pages
		the claims,	Nos.
		the drawings,	sheets/fig.
5.	CO:	nsidered to go bey	on established as if (some of) the amendments had not been made, since they have been ond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).
Replace	ment sheets s "originall	which have been fu	rnished to the receiving Office in response to an invitation under Article 14 are referred to in this



International application No.

#### PCT/AU99/00562

V. Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1.	Statement			
	Novelty (N)	Claims	3 to 7, 10, 13, 15 to 18	YES
		Claims	1 ,8, 9, 11, 12, 14	NO
	Inventive step (IS)	Claims	10, 17	YES
		Claims	1 to 9, 11 to 16, 18	NO

Industrial applicability (IA) Claims 1 to 18

YES

Claims

#### 2. Citations and explanations

#### NOVELTY (N) Claims 1, 8, 9, 11, 12, 14

AU 13469/95 A

The above citation discloses all the features of the claims listed above.

This citation is directed to insulating structures per se (the wall of a dwelling being merely one example) and which would include process vessels.

The citation is directed not to a specific field of application but rather to a desired result an hence a person considering insulating the process vessel would consider this document relevant.

## INVENTIVE STEP (IS) Claims 1 to 9, 11 to 16, 18

Claims 1, 8, 9, 11, 12, 14 as above.

Claims 2 to 7, 13, 15, 16, 18: the features added by these claims amount to common general knowledge and hence do not involve an inventive step.

#### INDUSTRIAL APPLICABILITY (IA) Claims 1 to 18

All claims are considered to be industrially applicable.



International application No. PCT/AU99/00562

M.

#### Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

- 1. Claim 1 is not clear with regard to the phrase beginning "none of which..." and whether the limitation ends. Do the fastening components not only not extend continuously about the periphery but also not space from the outer wall.
- 2. Claim 1 is not clear with regard to the relationship between the outer surface layer of the panel and the thermal insulation layer and the process vessel. That is on which side of the panel is the thermal insulation and is the panel or the thermal insulation closest to the process vessel.
- 3. Claim 17 is not clear with regard to the phrase 'the outer surface of a conical section there of' an what this is referring to.



## Please reply to Perth office

July 17, 2000

Our Ref:

P16178PC00 RHB:JAM

Commissioner of Patents IP Australia

Dear Sir,

Re:

International PCT Application No. PCT/AU99/00562 by

**Bains Harding Limited** 

We refer to the Written Opinion, which issued upon the above application on February 24, 2000, and on which the deadline for response has been extended to July 24, 2000.

## Proposed Amendments

Please substitute pages 2 and 7 of the specification with the replacement pages 2, 2a, 7 and 7a enclosed with this letter. Claim 1 is proposed to be amended to further clarify the distinction of that claim from the prior art. Claim 7 is proposed to be amended to clarify that the "outer surface layer" referred to is that of the panel. Both claim amendments are supported by the specification (see page 3, line 21; page 4, lines 1 to 3; page 5, line 27 to page 6, line 3; and Figures 1 and 2 thereof). The amendment to page 2 is consequential upon the claim amendment.

# Distinguishing the Claims from the Prior Art

The claims, as amended, are novel and inventive over the prior art.

# Nature of the Invention

The invention comprises an insulation module for a process vessel, which includes an externally mounted pre-fabricated panel having an outer surface layer. A thermal insulation layer is secured to the outer surface layer. The panel is pre-fabricated and mounted directly to the process vessel by a simple fastening system of complementary fastening components such as brackets, washers and fixing screws. The panel is so mounted as to leave an air gap between the insulating panel and outer wall of the process vessel.

Patent and Trade Mark Attorneys in Australia and New Zealand Established 1859

#### **Principals**

Richard Baddeley BE (Chem) (Hons)
Michael Chin Quan BE (Hons) M Eng Sc
Peter Franke BSc LL B
Louis Gebhardt BSc
Carolyn Harris BSc (Hons)
Stephen Plymin BE (Mech)
Christian Schieber Dipt-Ing
(IM Aem 8 Space Tech Eng European Patent Attorne)
Ian Scott Dip App Chem
Karen Sinclair BSc
Richard Smoorenburg BE (Electronic)

Paul Fong 8 Eng (Comp Sys)
Amanda Jones 8 App Sc Dip IP Law
Kathy Leviton 8Sc (Analysical Science)(Hons)
Scott Martin 8E (Mach)
Scanolyn McCausland 8E (Elec)(Hons)
Carolyn Rolls 8Sc (Hons) Ph D Dip IP Law
Roger Syn 8E (Materiat)
Ray Tettman 8E (Dec) Grad Dip Mgt

Richie Paul BA (Chem) Ph D European Patent Attorney only

#### Melbourne

The Glasshouse
290 Burwood Road Hawthorn
Victoria 3122 Australia
Postal address:
Locked Bag 5 Hawthorn
Victoria 3122 Australia
Telephone +613 9819 1664
Facsimile +613 9819 6010

#### Sydney

Unit 1 The Village Riverside Corporate Park 39–117 Delhi Road North Ryde New South Wales 2113 Australia Telephone +612 9888 6600 Facsimile +612 9888 7600

#### Perth

4th Floor Durack Centre 263 Adelaide Terrace Perth Western Australia 6000 Australia Telephone +618 9325 1900 Facsimile +618 9325 4463

#### Email

mail@watermark.com.au Internet www.watermark.com.au

## AU 13469/95

This application is directed to household insulation, a different art from insulation of process vessels. The wall of a dwelling is not analogous to the wall of a process vessel.

## **DE 4225448**

This document is likewise not relevant. The insulation system is refractory in nature being placed on the inside wall of a hot gas duct. This bears no resemblance to the non-refractory externally mounted insulation module of the present invention.

## SU 1104339

This reference is likewise not directed to a modular construction of insulation including panels of the kind recited in the claims of the current application. Rather, an insulation jacket is taught which is merely spaced from, and not connected to, the piping. It may also be noted that the claims of this application have also been amended to exclude the possibility that the panel extend around the whole periphery of the process vessel. It may be noted that the shell insulation of the citation is slid over the section of pipe. Such a construction is further distinguished from the present invention by the exclusion of a construction in which the insulation layer opposes all of the outer wall of the process vessel.

## SU 706271

This document may be distinguished in two ways. First, a rail cistern is not a process vessel of the kind with which the Applicant is concerned. Second, the jacket is not apparently connected to the outer wall of the inner "cistern". Again, as far as can be seen, the system is not modular in construction and there is no panel which has a surface opposing only portion of the inner cistern outer wall.

## SE 8809482

This reference may likewise be distinguished from the claims of the present application. There is no evidence of a modular construction and there is no gap between the insulating layer and the outer wall of a process vessel.

## JP 08014483

This application is again not relevant being directed to insulation of a "superlow temperature refrigerator". Magnets 6 would not connect the insulating panel of the present invention to the outer wall of a process vessel in accordance with the present application.

Furthermore, because the insulation material is installed immediately against the outer wall surface of the vessel, and because the insulation material can retain moisture, this can potentially lead to corrosion problems for the vessel. Summary of the Invention

It is therefore an object of the present invention to avoid at least one of the above-noted disadvantages of existing insulation systems.

With this object in view, according to one aspect of the present invention, there is provided an insulation module for a process vessel including

an externally mounted pre-fabricated panel having integrally formed therein 10 an outer surface layer, and a thermal insulation layer which opposes a portion of an outer wall of the process vessel; and

mounting means comprising a fastening system of complementary fastening components, none of which extend continuously about a periphery of the process vessel extending from the panel to the vessel for directly mounting the panel at a distance from the outer wall of the process vessel, to define an air gap between the panel and the outer wall of the process vessel when the insulation module is mounted relative thereto.

The provision of the air gap leads to a number of advantages:

- (a) because the insulation layer is separated from the wall of the vessel
   20 by the air gap, this minimises the possibility of corrosion due to the retention of moisture within the insulation layer
  - (b) the air located within the air gap provides an additional insulation layer. This means that the insulation layer secured to the outer surface layer can be of a reduced thickness.
- 25 Furthermore, because the insulation layer is secured to the outer surface layer prior to insulation of the insulation module, the insulation layer can be treated to prevent the release of potentially hazardous fibres therefrom. For example, the insulation layer may be covered by material prior to securing to the outer surface layer. Alternatively, an adhesive paint may be sprayed on the outer surface of the insulation layer to prevent or minimise the release of fibres from that layer prior to securing to the outer surface layer. The applicant's co-pending

Australian Patent Application No. 26034/99 discloses a suitable sealing agent for this application of reducing fibre release.

The outer surface layer is dependent on the requirements of the plant

## THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An insulation module for a process vessel including:

an externally mounted pre-fabricated panel having integrally formed therein an outer surface layer and a thermal insulation layer which opposes a portion of the outer wall of the process vessel; and

mounting means comprising a fastening system of complementary fastening components, none of which extend continuously about the periphery of the process vessel for directly mounting the panel at a distance from the outer wall of said process vessel to define an air gap between the panel and the outer wall of the process vessel when the insulation module is mounted relative thereto.

- 2. The insulation module of claim 1 wherein said insulation layer is a fibrous material treated to prevent escape of fibres.
- 3. The insulation module of claim 1 or 2 wherein said insulation layer is retained between the outer surface layer and a support mesh.
- 4. The insulation module of claim 3 wherein fastening means extend between the outer surface layer through the insulation layer to the supporting mesh.
- 5. The insulation module of claim 4 wherein said fastening means is at least one fixing screw.
- 6. The insulation module of claim 5 wherein a speed clip member is secured to a free end of said at least one fixing screw.
- 7. The insulation module of any one of the preceding claims wherein the insulation layer is adhered directly to the outer surface layer of said panel.

8. The insulation module of any one of the preceding claims wherein said mounting means includes a series of brackets secured to and extending from the outer surface layer towards the vessel wall when the insulation is in an installed position.

- 16. The method of claim 15 wherein said fibrous material is treated with a sealing agent, optionally an acrylic emulsion.
- 17. The method of any one of claims 14 to 16 wherein said outer surface of said vessel includes the outer surface of a conical section thereof.
- 18. A process vessel insulated in accordance with the method of any one of claims 14 to 17.

# DATED this 17<sup>th</sup> day of July 2000 BAINS HARDING LIMITED

WATERMARK PATENT & TRADEMARK ATTORNEYS

4<sup>™</sup> FLOOR DURACK CENTRE

263 ADELAIDE TERRACE

PERTH WA 6000



### Please reply to Perth office

August 21, 2000

Our Ref:

P16178PC00 RHB:JAH

Commissioner of Patents IP Australia

Dear Sir.

Re:

International PCT Application No. PCT/AU99/00562 by

**Bains Harding Limited** 

We refer to the Written Opinion which issued upon the above application on 16 August 2000.

Please find enclosed a revised statement of claims which addresses the clarity issues raised at paragraph VIII. In addition, further recitation of the process vessel – as supported by the description at page 1, lines 10 to 14 – has been inserted into independent claims 1 and 14.

# The Reference - AU 13497/95

This application is entitled "Method of Insulating Structures" but following the title, there is a rapid departure in philosophy of insulation in the present case as compared with the reference.

The reference confines its disclosure by particular reference to the "insulation of walls of dwellings or structures" (see page 2, lines 2 to 7). Then it is said, at page 2, lines 12 to 15:

"A particular problem exists in that regard in relation to buildings having walls constructed of concrete, brick, stone or other masonry material. With such dwellings there is a difficulty in securing insulation to a surface of a wall, for example".

Process vessels may be completely distinguished from such structures. Accordingly, an important distinction between the amended claims and the reference is further enlivened by the requirement that the process vessel contain a material to be maintained within controlled temperature limits for use in a process. This is nowhere taught in the reference and so novelty is conferred on all claims.

Patent and Trade Mark Attorneys in Australia and New Zealand Established 1859

Principals

Richard Baddeley & Chemi (Hons) Michael Chin Quan & Chons) Ming Sc Peter Franke & Li & Louis Gebhardt & Sc Carolyn Harris & Chons) Stephen Plymin & (Mech) Christian Schieber Dipling (MAen & Space Tech Engl European Patent Attori In Scott Dip App Chem Karen Sinclair & Sc Richard Smoorenburg & Electronic

Paul Fong 8 Eng (Comp Syst)
Amanda Jones 8 App Sc Dip IP Low
Kathy Leviton 85c (Analytical Science)(Hons
Scott Martin 85 (Mech)
Susan McCausland 85 (Elec)(Hons)
Carolyn Rolls 85c (Hons) Ph D Dip IP Low
Roger Syn 85 (Materiels)
Ray Tettman 85 (Dec) Grad Dip Mgt

Richie Paul BA (Chem) Ph D European Patent Attorney only

#### Melbourne

The Glasshouse
290 Burwood Road Hawthom
Victoria 3122 Australia
Postal address:
Locked Bag 5 Hawthorn
Victoria 3122 Australia
Telephone +613 9819 1664
Facsimile +613 9819 6010

#### Sydney

Unit 1 The Village Riverside Corporate Park 39–117 Delhi Road North Ryde New South Wales 2113 Australia Telephone +612 9888 6600 Facsimile +612 9888 7600

#### Perth

4th Floor Durack Centre 263 Adelaide Terrace Perth Western Australia 6000 Australia Telephone +618 9325 1900 Facsimile +618 9325 4463

#### Emai

mail@watermark.com.au Internet www.watermark.com.au

..../2

As to inventive step, one skilled in the art of insulating process vessels would not refer to prior art concerned with the problem of connecting insulation to masonry of dwellings. Process vessel insulation is a discrete art which may be totally distinguished from domestic insulation. This distinction is further emphasised by further recitation of the nature of a process vessel in the claims.

Favourable reconsideration of the application is respectfully requested.

Yours respectfully, WATERMARK

Richard H. Baddeley

Enc.

## THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An insulation module for a process vessel for containing a material to be maintained within controlled temperature limits for use in a process including:

an externally mounted pre-fabricated panel having integrally formed therein an outer surface layer and a thermal insulation layer which opposes a portion of the outer wall of the process vessel; and

mounting means comprising a fastening system of complementary fastening components, none of which extend continuously about the periphery of the process vessel, for directly mounting the panel at a distance from the outer wall of said process vessel to define an air gap between the panel and the outer wall of the process vessel when the insulation module is mounted relative thereto.

- 2. The insulation module of claim 1 wherein said insulation layer is a fibrous material treated to prevent escape of fibres.
- 3. The insulation module of claim 1 or 2 wherein said insulation layer is retained between the outer surface layer and a support mesh.
- 4. The insulation module of claim 3 wherein fastening means extend between the outer surface layer through the insulation layer to the supporting mesh.
- 5. The insulation module of claim 4 wherein said fastening means is at least one fixing screw.
- 6. The insulation module of claim 5 wherein a speed clip member is secured to a free end of said at least one fixing screw.
- 7. The insulation module of any one of the preceding claims wherein the insulation layer is adhered directly to the outer surface layer of said panel.

- 8. The insulation module of any one of the preceding claims wherein said mounting means includes a series of brackets secured to and extending from the outer surface layer towards the vessel wall when the insulation is in an installed position.
- 9. The insulation module of claim 8 wherein each bracket includes a mounting leg for supporting the panel of the insulation module away from the vessel wall.
- 10. The insulation module of claim 9 wherein said vessel has a series of cleats provided about the outer wall thereof and said mounting legs of said brackets are secured to said cleats.
- 11. The insulation module of claim 9 wherein fastening means secure said bracket mounting legs to the vessel wall.
- 12. The insulation module of claim 11 wherein said fastening means are thread rod stubs and each bracket mounting leg includes at least one laterally extending foot having at least one opening therethrough to accommodate respective thrread rod stubs.
- 13. The insulation module of any one of the preceding claims wherein said insulation layer is of material selected from the group consisting of rock wool, fibreglass, PIR foam, PUR form and mixtures thereof.
- 14. A method of installing insulation on a process vessel for containing a material to be maintained within controlled temperature limits for use in a process including mounting a plurality of insulation modules, each as claimed in any one of claims 1 to 13 in an abutting or closely adjacent relationship on an outer surface of the vessel, each insulation module including a panel having an outer surface layer, and an insulation layer secured to the outer surface layer, and

mounting means extending from the panel for mounting the insulation module on an outer wall of the vessel, wherein the method includes securing the mounting means to the vessel to thereby provide an air gap between the insulation layer and the outer wall of the vessel when the insulation modules are mounted relative thereto.

- 15. The method of claim 14 wherein said insulation layer is of fibrous material treated to prevent release of fibres.
- 16. The method of claim 15 wherein said fibrous material is treated with a sealing agent, optionally an acrylic emulsion.
- 17. The method of any one of claims 14 to 16 wherein said outer surface of said vessel includes the outer surface of a conical section of the vessel.
- 18. A process vessel insulated in accordance with the method of any one of claims 14 to 17.

Furthermore, because the insulation material is installed immediately against the outer wall surface of the vessel, and because the insulation material can retain moisture, this can potentially lead to corrosion problems for the vessel. Summary of the Invention

It is therefore an object of the present invention to avoid at least one of the above-noted disadvantages of existing insulation systems.

With this object in view, according to one aspect of the present invention, there is provided an insulation module for a process vessel including

an externally mounted pre-fabricated panel having integrally formed therein 10 an outer surface layer, and a thermal insulation layer which opposes a portion of an outer wall of the process vessel; and

mounting means comprising a fastening system of complementary fastening components, none of which extend continuously about a periphery of the process vessel extending from the panel to the vessel for directly mounting the panel at a distance from the outer wall of the process vessel, to define an air gap between the panel and the outer wall of the process vessel when the insulation module is mounted relative thereto.

The provision of the air gap leads to a number of advantages:

- (a) because the insulation layer is separated from the wall of the vessel
   20 by the air gap, this minimises the possibility of corrosion due to the retention of moisture within the insulation layer
  - (b) the air located within the air gap provides an additional insulation layer. This means that the insulation layer secured to the outer surface layer can be of a reduced thickness.
- 25 Furthermore, because the insulation layer is secured to the outer surface layer prior to insulation of the insulation module, the insulation layer can be treated to prevent the release of potentially hazardous fibres therefrom. For example, the insulation layer may be covered by material prior to securing to the outer surface layer. Alternatively, an adhesive paint may be sprayed on the outer surface of the insulation layer to prevent or minimise the release of fibres from that layer prior to securing to the outer surface layer. The applicant's co-pending

Australian Patent Application No. 26034/99 discloses a suitable sealing agent for this application of reducing fibre release.

The outer surface layer is dependent on the requirements of the plant

## THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An insulation module for a process vessel including:

an externally mounted pre-fabricated panel having integrally formed therein an outer surface layer and a thermal insulation layer which opposes a portion of the outer wall of the process vessel; and

mounting means comprising a fastening system of complementary fastening components, none of which extend continuously about the periphery of the process vessel for directly mounting the panel at a distance from the outer wall of said process vessel to define an air gap between the panel and the outer wall of the process vessel when the insulation module is mounted relative thereto.

- 2. The insulation module of claim 1 wherein said insulation layer is a fibrous material treated to prevent escape of fibres.
- 3. The insulation module of claim 1 or 2 wherein said insulation layer is retained between the outer surface layer and a support mesh.
- 4. The insulation module of claim 3 wherein fastening means extend between the outer surface layer through the insulation layer to the supporting mesh.
- 5. The insulation module of claim 4 wherein said fastening means is at least one fixing screw.
- 6. The insulation module of claim 5 wherein a speed clip member is secured to a free end of said at least one fixing screw.
- 7. The insulation module of any one of the preceding claims wherein the insulation layer is adhered directly to the outer surface layer of said panel.



8. The insulation module of any one of the preceding claims wherein said mounting means includes a series of brackets secured to and extending from the outer surface layer towards the vessel wall when the insulation is in an installed position.

- 16. The method of claim 15 wherein said fibrous material is treated with a sealing agent, optionally an acrylic emulsion.
- 17. The method of any one of claims 14 to 16 wherein said outer surface of said vessel includes the outer surface of a conical section thereof.
- 18. A process vessel insulated in accordance with the method of any one of claims 14 to 17.

# **DATED** this 17<sup>th</sup> day of July 2000 BAINS HARDING LIMITED

WATERMARK PATENT & TRADEMARK ATTORNEYS

4<sup>TH</sup> FLOOR DURACK CENTRE

263 ADELAIDE TERRACE

PERTH WA 6000

